



Tumble Dryers series

Feature:

- Computer-controlled operating procedures, cold air、hot air time setting, the temperature can be programmed;
- The unique belt- drive system structure, low noise, stable operation;
- Low-power drive motor, powerful exhaust fan configuration;
- Stainless steel dryer drum design, smooth appearance, high strength;
- Main parts are advanced brand, to ensure safety, durable and reliable.

Technical Specifications:

Model	Capacity (kg/lbs)	Motor power (kw)	Heating Power			Equipment weight (kg)	Dimensions (mm) (WxDxH)
			Electric power(kw)	Steam heating(kg/h)	Gas heating(Btu/h)		
GZ-100	100/220	3.7	66	150	361000	1000	1510 × 2035 × 2505
GZ-70	70/154	3	54	100	258000	880	1410 × 1825 × 2430
GZ-50	50/110	2.25	40.5	90	180000	800	1185 × 1680 × 2235
GZ-35	35/77	0.5	27	50	155000	420	986 × 1370 × 1953
GZ-25	25/55	0.5	22.5	40	129000	400	967 × 1195 × 1908
GZ-18	18/40	0.5	18	27	105000	380	887 × 1166 × 1636



» Steam Heating System



» Electric Heating System



» Belt-Drive System



» Gas Heating System

*Optional
different heating function*

GUANGZHOU WEIERSHI WASHING MACHINERY CO., LTD
Address: Caohe Industrial Area, Panyu District, Guangzhou Zip

Code: 511483

Tel: +86 20-84626702 84644418

Web: www.gzweiershi.com.cn

E-mail: weiershi@gzweiershi.com.cn

Our company reserves the right to change design and specifications without notice.

Technical Specifications



MODEL		GZ-18	GZ-25	GZ-35	GZ-50	GZ-70	GZ-100
Capacity	kg/lbs	18/40	25/55	35/77	50/110	70/154	100/220
Cylinder Diameter	mm	790	910	940	1120	1300	1410
Cylinder Depth	mm	720	740	915	1060	1060	1200
Cylinder Volume	l	352	480	635	1043	1410	1873
Door opening size	mm	640	640	640	840	840	840
Door center to floor	mm	630	780	790	825	880	915
Power supply	V/Hz/Ph	380V/50HZ/3PH					
Basket Motor Power	Kw	0.25	0.25	0.25	0.75	1.5	1.5
Blower Motor power	Kw	0.25	0.25	0.25	1.5	1.5	2.2
Elec.Heating	Kw	18	22.5	27	40.5	54	66
Steam Pressure	Mpa	0.6	0.6	0.6	0.6	0.6	0.6
Steam Inlets	Inch/mm	3/4	3/4	3/4	3/4	1	1
Steam Outlets	Inch/mm	3/4	3/4	3/4	3/4	1	1
Max.Steam Consumption	kg/cycle	27	40	50	90	100	150
Gas Pressure LP	mbar	30	30	30	30	30	30
Gas supply	Inch/mm	1/2	1/2	1/2	3/4	3/4	2x3/4
Gas Heat Input	Btu/hr	105000	129000	155000	180000	258000	361000
Exhaust Vent Diameter	mm	Φ200	Φ200	Φ200	Φ300	Φ300	Φ300
Exhaust Height Floor	mm	310	315	385	387	276	276
Flow Rate	m ³ /hr	810	1200	1800	3500	3900	4200
Dimension							
Width	mm	887	967	986	1185	1410	1510
Depth	mm	1166	1195	1370	1680	1825	2035
Height	mm	1636	1908	1953	2235	2430	2505
Net weight	Kg	380	400	420	800	880	1000
Shipping Dimension							
Width	mm	930	1010	1030	1200	1440	1540
Depth	mm	1300	1305	1480	1780	1930	2045
Height	mm	1750	2030	2073	2355	2200	2280
Gross Weight	Kg	410	435	470	870	960	1100