

M 501 - 502



**MANICHINI UNIVERSALI
UNIVERSAL FORM FINISHERS
MANNEQUINS UNIVERSALS
MANIQUIS UNIVERSALES
BÜGELPUPPEN
УНИВЕРСАЛЬНЫ МАНЕКЕНЫ**

+ M 502
GIACCA/JACKET



+ M 502
GIACCA/JACKET



+ M 502
GIACCA A VENTO/ANORAK



+ M 502
CAPPOTTO/COAT



+ M 502
PINZE/PLIERS



M 501 - 502



The M 501 tensioning form finisher has been designed to fulfil demands of a Wet Cleaning pressing system that requires vertical tensioning for perfect seam finishing and fabric "revitalising". Suitable for jackets, coats, raincoats, lumber jackets, leather garments, dresses and also many other speciality applications of any fabric and size. It features a special tensioning system for the garment being processed and the powerful hot air flow provides a high class finish. Automatic positioning of the dummy is accomplished using a photocell. A powerful and flexible microprocessor allows cycles to be programmed and saved.

It is supplied ready for connection to an external steam supply. Using the M 501 for dry cleaned garments, a very high standard of finish will be achieved.

Any final touching-up (if at all) is restricted to very minor details. Using the M 501, you will see improved hourly output and significantly, no specialised labour is required to produce excellent results

M 501

With microprocessor cycle control, up to 10 programs storage capacity. Available with either a fixed dummy or with a 270° rotating dummy. Available options (upon request).

M 502

With PLC system as standard allowing up to 10 programs to be customised and saved, a 270° rotating dummy; lateral and rear pneumatic clamps for vents.



Available extras upon request:

- GFV steam iron assembly complete with ALL STEAM iron for final touch-up.

TECHNICAL DATA	M 501 - M 502
REQUIRED POWER	400 V/3+N/50Hz* 220 V/3/60 Hz
FAN MOTOR	1,1 kW
STEAM INLET	1/2"
RETURN OUTLET	1/2"
STEAM WORKING PRESSURE	5 ÷ 6 bar - 70 ÷ 87 psi
STEAM CONSUMPTION	15 ÷ 20 kg/h 33 ÷ 44 Lbs/h
AIR INLET	1/4"
AIR WORKING PRESSURE	6 ÷ 7 bar - 87 ÷ 100 psi
AIR CONSUMPTION	10 NL/min - 0,35 cubic feet/cycle
ENCUMBRANCE	1120x1280x2290 max ÷ 1530 min mm 44x50x93 max ÷ 63min in
NET WEIGHT	130 kg - 287 Lbs
GROSS WEIGHT	160 kg - 353 Lbs
OVERALL DIMENSIONS	970 x 880 x 1760 mm 38 x 35 x 70 in
VOLUME	1,5 m3 - 53 Ft3

*Other voltages by request.

For manufacturing necessities the above-mentioned specifications are not binding.

