



W series double tilting automatic washer extractor

Feature:

- Simple and convenient operating system
computer control panel with touch screen technology, microcomputer control, fully self-testing, a variety of common faults of operation tips, 49 sets of computer programs, easy to learn and operate, and meet users' needs;
- Appropriate speed, high efficiency;
Single inverter drive to provide the necessary speed, high-speed dehydration on speed 650rpm can provide 310G powers, thereby reducing drying time, improve the efficiency of laundry;
- Save time and effort but enhance efficiency;
Bi-directional tilt automatic washer extractor design for improving the efficiency of laundry room, it was designed with bi-directional tilt function before and after, providing efficient, simple and safe operation, and high quality of washing effect.
- Outstanding drum design;
Drum has more range of small holes, it makes washing quality better, rinsing and dry effect faster and better, spacious drum has provided large space for washing, also let clothing expand to absorb soap liquid fully. Drum's intensive blowhole will spray more water on clothing to scour stains.



Select different method of loading and unloading, can tilt.



➤ Optional accessory LCD Digital Dashboard

Technical Specifications:

| Model | Capacity (kg/lbs) | Drum size (Φ x L)mm | Voltage (V/Hz) | Motor power (kw) | Wash speed (rpm) | Spin speed (rpm) | Weight (kg) | Dimensions(mm) (WxDxH) |
|---------|-------------------|---------------------|----------------|------------------|------------------|------------------|-------------|------------------------|
| W2060FT | 60/132 | 1080 x 620 | 380/50 | 7.5 | 35 | 700 | 2350 | 1639 x 1607 x 2110 |
| W2110FT | 120/265 | 1300 x 820 | 380/50 | 15 | 33 | 650 | 4300 | 1840 x 2055 x 2265 |

GUANGZHOU WEIERSHI WASHING MACHINERY CO., LTD

Address: Caohu Industrial Area, Panyu District, Guangzhou Zip

Code: 511483

Tel: +86 20-84626702 84644418

Web: www.gzweiershi.com.cn

E-mail: weiershi@gzweiershi.com.cn

Our company reserves the right to change design and specifications without notice.

Technical Specifications



| MODEL | | W2030F | W2060F | W2060FT | W2110F | W2110FT |
|--------------------|---------|----------|----------|----------|----------|----------|
| Capacity | kg/lbs | 25/55 | 60/132 | 60/132 | 120/265 | 120/265 |
| DRUM | | | | | | |
| Volume | mm | 226 | 568 | 568 | 1088 | 1088 |
| Diameter | mm | 738 | 1080 | 1080 | 1300 | 1300 |
| Depth | mm | 530 | 620 | 620 | 820 | 820 |
| DOOR | | | | | | |
| Door Opening | mm | 397 | 558 | 558 | 684 | 684 |
| Door to Floor | mm | 630 | 925 | 1090 | 920 | 1110 |
| SPEED ADJUSTABLE | | | | | | |
| Wash | RPM | 39-43 | 35 | 35 | 33 | 33 |
| Distribution | RPM | 87 | 78 | 78 | 75 | 75 |
| Low Extract | RPM | 400 | 400 | 400 | 350 | 350 |
| High Extract | RPM | 750 | 700 | 700 | 650 | 650 |
| POWER | | | | | | |
| Voltage Supply | V/Ph/Hz | 380/3/50 | 380/3/50 | 380/3/50 | 380/3/50 | 380/3/50 |
| Motor | KW | 2.2 | 7.5 | 7.5 | 15 | 15 |
| Inverter | KW | 2.2 | 7.5 | 7.5 | 15 | 15 |
| HEATING | | | | | | |
| Electricity | KW | 19.5 | 39 | 39 | / | / |
| STEAM | BAR | 2-4 | 2-4 | 2-4 | 2-4 | 2-4 |
| G-FORCE | | | | | | |
| Low Extract | G | 250 | 315 | 315 | 310 | 310 |
| High Extract | G | 300 | 385 | 385 | 380 | 380 |
| CONNECTIONS | | | | | | |
| Water Inlet | DN | 20 | 25 | 25 | 50 | 50 |
| Steam Inlet | DN | 15 | 20 | 20 | 25 | 25 |
| Drain Connection | DN | 80 | 80 | 80 | 110 | 110 |
| Compressed Air | mm | / | Φ6 | Φ6 | Φ6 | Φ6 |
| MACHINE DIMENSIONS | | | | | | |
| Width | mm | 1040 | 1580 | 1639 | 1765 | 1840 |
| Depth | mm | 1236 | 1495 | 1607 | 1935 | 2055 |
| Height | mm | 1450 | 1917 | 2110 | 2060 | 2265 |
| MACHINE WEIGHT | | | | | | |
| Net Weight | kg | 780 | 1900 | 2350 | 3800 | 4300 |